



**WICHITA STATE  
UNIVERSITY**

**UNIVERSITY LIBRARIES**

## **Brain-computer interface to control a 6 DOF robotic arm**

Item Type	Abstract
Authors	Don, Thisath Attampola Arachchige
Citation	Don, T. A. A. 2021. Brain-computer interface to control a 6 DOF robotic arm -- In Proceedings: 17th Annual Symposium on Graduate Research and Scholarly Projects. Wichita, KS: Wichita State University
Publisher	Wichita State University
Download date	2026-05-19 07:28:26
Link to Item	<a href="https://soar.wichita.edu/handle/10057/19912">https://soar.wichita.edu/handle/10057/19912</a>

# Brain-Computer Interface to Control a 6 DOF Robotic Arm

Thisath Attampola Arachchige Don<sup>1</sup>

Faculty: Yimesker Yihun,<sup>1</sup> Jaydip Desai<sup>2</sup>

<sup>1</sup>*Department of Mechanical Engineering, College of Engineering*

<sup>2</sup>*Department of Biomedical Engineering, College of Engineering*

In this study, a brain-computer interface (BCI) system is developed to control a six degrees of freedom robot arm. Such interface systems have a potential application in space missions for astronauts to have supplemental human-robot communication platform. Also, such human-robot interface system can be used to aid and enhance the quality of life for people with disability. However, decoding brain signal information into multi-degree of freedom system is a real challenge as the signals are easily affected by noise and crosstalk. In this research, an integrated electroencephalogram (EEG) and near-infrared spectroscopy (fNIR) system is used to record the brain's electrical activity and its blood-oxygen-level dependent (BOLD) responses. Then an algorithm has been developed and used to classify the signals related to six different directional intents. These six different features were utilized to command a robot manipulator to follow the six directional motions (left-right, up-down, and in-out). The task planning, robot kinematics and dynamics are computed using MATLAB/SIMULINK environment. Polynomial based inverse kinematic approach is applied to find the corresponding robot joint positions. The integrated system was simulated in a virtual environment using unity software. The preliminary result has shown the feasibility of decoding brain signals to create a BCI systems for the control of multi-degrees of freedom robotic system.